



TUBES SANS SOUDURE PÉTROLE SCHEDULE 80S - 160 - XXS

DN	Diamètre		Schedule 80S			Schedule 160			XXS		
	Pouce	(diamètre extérieur (mm))	80S	mm	kg/m	160	mm	kg/m	XXS	mm	kg/m
6	1/8"	10,29	80S	2,41		160			XXS		
8	1/4"	13,70	80S	3,02		160			XXS		
10	3/8"	17,10	80S	3,20		160			XXS		
15	1/2"	21,34	80S	3,73	1,64	160	4,75	1,97	XXS	7,47	2,59
20	3/4"	26,67	80S	3,91	2,22	160	5,54	2,93	XXS	7,82	3,69
25	1"	33,40	80S	4,55	3,28	160	6,35	4,29	XXS	9,09	5,52
32	1 1/4"	42,16	80S	4,85	4,52	160	6,35	5,68	XXS	9,70	7,87
40	1 1/2"	48,26	80S	5,08	5,48	160	7,14	7,34	XXS	10,16	9,68
50	2"	60,33	80S	5,54	7,58	160	8,71	11,23	XXS	11,07	13,62
65	2 1/2"	73,03	80S	7,01	11,57	160	9,53	15,13	XXS	14,02	20,68
80	3"	88,90	80S	7,62	15,48	160	11,13	21,64	XXS	15,24	28,06
90	3 1/2"	101,60	80S	8,08	18,89	160			XXS	16,15	
100	4"	114,30	80S	8,56	22,63	160	13,49	34,00	XXS	17,12	41,59
125	5"	141,30	80S	9,53	31,39	160	15,88	49,79	XXS	19,05	58,22
150	6"	168,30	80S	10,97	43,15	160	18,26	68,49	XXS	21,95	80,31
200	8"	219,10	80S	12,70	65,53	160	23,01	112,80	XXS	22,23	109,41
250	10"	273,00	80S	12,70	82,65	160	28,58	174,64	XXS	25,40	157,23
300	12"	323,90	80S	12,70	98,81	160	33,32	242,05	XXS	25,40	189,55
350	14"	355,60	80S	12,70	108,87	160	35,71	285,58	XXS		
400	16"	406,40	80S	12,70	125,00	160	40,49	370,39	XXS		
450	18"	457,20	80S	12,70	141,13	160	45,24	465,93	XXS		
500	20"	508,00	80S	12,70	157,26	160	50,01	572,60	XXS		
600	24"	609,60	80S	12,70	189,52	160	59,54	818,76	XXS		
700	28"	711,20	80S	12,70	221,77	160			XXS		
800	32"	812,80	80S	12,70	254,03	160			XXS		
900	36"	914,40	80S	12,70	286,29	160			XXS		